PRODUCT DATA SHEET

ESGEM PA 9500

Neutralizing agent for aqueous paint systems

Summary

ESGEM PA 9500, is a low odour pH adjuster and stabilizing aid for water based paints and coatings.

Advantages

- Versatile pH neutralizing agent
- Ideal for wide range of water borne coating systems
- Provides long term pH stability to the system
- Effective replacement for ammonium hydroxide and other amine neutralizers
- Helps to prevent in-can and flash corrosion

Features

- Low odour product
- Low emissions and ease of handling
- Suitable for wide range of applications
- Cost effective

Storage

Stable under normal temperature and conditions

Health & Safety

Health and handling advice on these products is given in individual data sheets, available upon request

PRODUCT DATA SHEET

ESGEM PA 9500

Product Data:

Composition	Proprietary Composition
Appearance	Colourless to light Yellow Liquid
pH(as such)	Alkaline

Application Guidelines

ESGEM PA 9500, Shall be recommended in grinding or letdown stages of water-based paint formulations. Optimal dosage 0.1-0.3%. The dosage shall be optimized in case of high acidity systems based on the pre trials.

Contact

For feedback or further information, please feel free to contact us at info@tulonmaterials.com.

Tulon Materials Pvt Ltd

Address: A212, 2nd Floor, Plot No 11 and 11A, Punit Industrial Premises Industrial Area TTC, MIDC, Turbhe, Navi Mumbai – 400705

Website: www.tulonmaterials.com

The statements, technical information and recommendations contained herein are believed to be accurate as of the date hereof. Since the conditions and methods of use of the product and of the information referred to herein are beyond our control, Tulon Materials Pvt Ltd expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information; NO WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE, WARRANTY OF MERCHANTABILITY OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, IS MADE CONCERNING THE GOODS DESCRIBED OR THE INFORMATION PROVIDED HEREIN. Theinformation provided herein relates only to the specific product designated and may not be applicable when such product is used in combination with other materials or in any process. The user should thoroughly test any application before commercialization. Nothing contained herein constitutes a license to practice under any patent and it should not be construed as an inducement to infringe any patent and the user is advised to take appropriate steps to be sure that any proposed use of the product will not result in patent infringement. See SDS for Health & Safety Considerations. ESGAL® is a registered trademark of Tulon Materials Pvt Ltd

2025 Tulon Materials Pvt Ltd All rights reserved.